

Electro-Replacement Ltd 1 Moor Park Industrial Centre, Tolpits Lane, Watford, Hertfordshire, WD18 9EU

ISO 4 Pole

Isolator Switch

Efficiently designed 4-pole weather proof isolator switch offering safety, durability, and optimum performance.

Features:

- Voltage Compatibility: Up to 415V, suitable for single or 3-phase + neutral.
- **Amperage:** Designed for equipment isolation up to rated amps (20A / 35A / 45A / 63A).
- Base Mechanism: Provides easy termination
 with ample wiring space.
- Connector Bars: Fixed earth and neutral with dual clamping screws ensuring secure cable clamping.
- **Cable Insertion:** Unscrew caps for 2 x 25mm & 4 x 20mm cut-outs at the back.
- **Safety Caps:** Insulating caps protect mounting screws from live cables.
- Lock Feature: Isolators can lock in the off position.
- Durability: Impact-resistant base and cover for challenging installations.
- Seal: Weatherproof gasket between two sections.
- Design: Heavy-duty and suitable for indoor/ outdoor use.
- Protection Rating: IP66 Total protection from dust, oil, water jets, and accidental contact.
- **Knockouts:** 4x 25mm top/bottom and 2x 20mm adapters included.

Order Details:

Product Code	Amps
ISO204E/N	20A
ISO354E/N	35A
ISO454E/N	45A
ISO634E/N	63A



TECHNICAL DATA	ISO 4 Pole
Size	85mm (W) x 170mm (H) x 90mm (D)
Colour	Grey, yellow & red
Knockouts	4 x knockouts to rear (20mm) • 4 x screw-out cable entries - 2 top + 2 bottom (25mm)
Wall Mountable	Yes
Lockable	Lockable in OFF position
IP Rating	IP66
Included	Fixing kit & instructions
Weight	0.45kg
Inner Carton Quantity	1
Standards	BS EN 60947-3

Technical SupportSales01923 220 27701923 255 344technical@electroreplacement.comsales@electroreplacement.com

www.electroreplacement.com