



WEATHERPROOF EXIT BUTTON

EXIT BUTTONS

Market leading green dome button, that is both hard wearing and cost effective. Suitable for use in applications up to 30V.



WP-EBSS25/PTE

SPECIFICATION	FEATURES	OTHER PRODUCTS
---------------	----------	----------------


WP-EBSS25

- Contacts: Double pole N/O - N/C
- Output: 4 AMP contact @ 30V AC/DC
- Wear resistant legend
- External use
- Rated IP65 ingress protection
- Silver contacts
- Operating temperature -20° to +60°c
- Operating travel: 2mm
- Contact resistance: 10m OHM (Max)
- Operating life (mechanical): 1,000,000


WP-EBSS25

- Stainless Steel Button
- Momentary operation / contact
- High impact plastic back box
- Surface fitting
- Easy clean surface
- Ideal for general / sensitive areas
- Gasket and gland included
- Screw footprint for flush fitting onto standard back box
- Distance between fixing holes 60mm

IEPS/PTE



AH600



DIMENSIONS	CONTENTS
------------	----------

WP-EBSS25

- 85H x 85W x 40/50D (mm)
- 248g (Boxed)
- 200g (Unboxed)

WP-EBSS25

- Stainless Steel Exit Button
- Stainless Steel Plate (2mm)
- 2 Security Screws
- Allen Key
- Surface Box
- Gland
- Gasket

ML600




JMB/KS-1

